

# AXIS Q6055 PTZ Dome Network Camera

Indoor PTZ with HDTV 1080p, 32x zoom and Zipstream

AXIS Q6055 is a top-of-the-line, indoor PTZ dome with HDTV 1080p, 32x optical zoom, and fast and precise pan/tilt performance for wide area coverage and detailed surveillance at great distances. The high light sensitivity and day/night functionality ensure high image quality even in low-light conditions, while Axis Zipstream technology reduces bandwidth and storage requirements. With guard tour, it is possible to direct the camera automatically to 256 preset positions. AXIS Q6055 comes with built-in video analytics such as highlight compensation, object removed, enter/exit detection, autotracking and Active Gatekeeper. It supports two-way audio, audio detection, I/O ports, and 24 V AC/DC power.

- > [HDTV 1080p and 32x optical zoom](#)
- > [Axis Zipstream technology](#)
- > [Built-in video analytics](#)
- > [IP52-rated protection against dust and dripping water](#)



# AXIS Q6055 PTZ Dome Network Camera

|  |   |                                   |  |
|--|---|-----------------------------------|--|
| <b>Models</b>                            | AXIS Q6055 60 Hz<br>AXIS Q6055 50 Hz  | <b>Event triggers</b>             | Detectors: live stream accessed, video motion detection, shock detection, audio detection<br>Object removed, enter/exit detector, fence detector, object counter<br>Hardware: fan, network, temperature<br>PTZ: autotracking, error, moving, ready, preset reached<br>Storage: disruption, recording<br>System: system ready<br>Time: recurrence, use schedule<br>Input signal: manual trigger, virtual input, digital input |
| <b>Camera</b>                            |   |                                   |  |
| <b>Image sensor</b>                      | 1/2.8" progressive scan CMOS  | <b>Event actions</b>              | Day/night mode, overlay text, video recording to edge storage, pre- and post-alarm video buffering, send SNMP trap<br>PTZ: PTZ preset, start/stop guard tour<br>File upload via FTP, SFTP, HTTP, HTTPS network share and email<br>Notification via email, HTTP, HTTPS and TCP<br>External output activation, audio recording to edge storage, play audio clip  |
| <b>Lens</b>                              | 4.44–142.6 mm, F1.6–4.41<br>Horizontal field of view: 62.8°–2.23°<br>Vertical field of view: 36.8°–1.3°<br>Autofocus, auto-iris   | <b>Data streaming</b>             | Event data   |
| <b>Day and night</b>                     | Automatically removable infrared-cut filter   | <b>Built-in installation aids</b> | Pixel counter  |
| <b>Minimum illumination</b>              | Color: 0.3 lux at 30 IRE F1.6<br>B/W: 0.03 lux at 30 IRE F1.6<br>Color: 0.5 lux at 50 IRE F1.6<br>B/W: 0.04 lux at 50 IRE F1.6  | <b>General</b>                    |  |
| <b>Shutter time</b>                      | 1/33000 s to 1/3 s with 50 Hz<br>1/33000 s to 1/4 s with 60 Hz  | <b>Casing</b>                     | IP52-rated<br>Metal casing (aluminum), Acrylic (PMMA) clear dome   |
| <b>Pan/Tilt/Zoom</b>                     | Pan: 360° endless, 0.05° – 450°/s<br>Tilt: 180°, 0.05°–450°/s<br>32x optical zoom and 12x digital zoom, total 384x zoom<br>E-flip, 256 preset positions, Tour recording, Guard tour, Control queue, On-screen directional indicator, Set new pan 0°, Adjustable zoom speed  | <b>Sustainability</b>             | PVC free   |
| <b>Video</b>                             |   |                                   |  |
| <b>Video compression</b>                 | H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles<br>Motion JPEG  | <b>Memory</b>                     | 512 MB RAM, 256 MB Flash   |
| <b>Resolution</b>                        | HDTV 1080p 1920x1080 to 320x180<br>HDTV 720p 1280x720 to 320x180  | <b>Power</b>                      | Axis PoE+ midspan 1–port: 100–240 V AC, max 37 W<br>IEEE 802.3at Type 2 Class 4<br>Camera consumption: typical 13 W, max 19 W<br><b>Multicable:</b><br>20–28 V DC, typical 11 W, max 16 W<br>20–24 V AC, typical 17 VA, max 25 VA  |
| <b>Frame rate</b>                        | Up to 50/60 fps (50/60 Hz) in HDTV 720p<br>Up to 25/30 fps (50/60 Hz) in HDTV 1080p   | <b>Connectors</b>                 | RJ45 10BASE-T/100BASE-TX PoE, multiconnector (cable sold separately) for AC/DC power, 4 configurable alarm inputs/outputs, mic in, line mono input, line mono output to active speaker   |
| <b>Video streaming</b>                   | Multiple, individually configurable streams in H.264 and Motion JPEG<br>Axis Zipstream technology<br>Controllable frame rate and bandwidth<br>VBR/MBR H.264   | <b>Storage</b>                    | Support for SD/SDHC/SDXC card<br>Support for SD card encryption<br>Support for recording to network-attached storage (NAS)<br>For SD card and NAS recommendations see <a href="http://www.axis.com">www.axis.com</a>   |
| <b>Image settings</b>                    | Manual shutter time, compression, color, brightness, sharpness, white balance, exposure control, exposure zones, fine tuning of behavior at low light, rotation: 0°, 180°, text and image overlay, 32 individual 3D privacy masks, image freeze on PTZ, automatic defog, backlight compensation<br>Wide Dynamic Range (WDR): Up to 120 dB depending on scene, highlight compensation                              | <b>Operating conditions</b>       | 0 °C to 50 °C (32 °F to 122 °F)<br>Humidity 10–85% RH (non-condensing)   |
| <b>Audio</b>                             |   |                                   |  |
| <b>Audio streaming</b>                   | Two-way: full duplex, half duplex, simplex  | <b>Storage conditions</b>         | –40 °C to 65 °C (–40 °F to 149 °F)   |
| <b>Audio compression</b>                 | AAC-LC 8/16 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz<br>Configurable bit rate  | <b>Approvals</b>                  | EMC<br>EN 55022 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 55024, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR 22 Class A, KCC KN32 Class A, KN35<br><b>Safety</b><br>IEC/EN/UL 60950-1<br><b>Environment</b><br>IEC/EN 60529 IP52, IEC 60721-4-3, IEC 60068-2<br><b>Midspan:</b> EN 60950-1, GS, UL, cUL, CE, FCC, VCCI, CB, KCC, UL-AR                         |
| <b>Audio input/output</b>                | Requires multicable (sold separately) for external microphone or line input, and line output  | <b>Weight</b>                     | Camera: 2.6 kg (5.7 lb); with drop-ceiling mount: 3.2 kg (7.1 lb)  |
| <b>Network</b>                           |   |                                   |  |
| <b>Security</b>                          | Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, Digest authentication, User access log, Centralized Certificate Management   | <b>Dimensions</b>                 | Hard-ceiling: Ø198 x 240 mm (Ø7 13/16 x 9 7/16 in)<br>Drop-ceiling: Ø248 x 243 mm (Ø9 3/4 x 9 9/16 in)   |
| <b>Supported protocols</b>               | IPv4/IPv6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP <sup>TM</sup> , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, NTCIP, LLDP  | <b>Included accessories</b>       | Axis PoE+ midspan 1–port, Recessed mount for hard and drop ceilings, Smoked dome cover<br>Installation Guide, Windows decoder 1-user license   |
| <b>System integration</b>                |   |                                   |  |
| <b>Application Programming Interface</b> | Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://www.axis.com">www.axis.com</a><br>AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF <sup>®</sup> Profile S and ONVIF <sup>®</sup> Profile G, specification at <a href="http://onvif.org">onvif.org</a>   | <b>Optional accessories</b>       | Multicable<br>AXIS T91 Mounting Accessories, AXIS T8415 Wireless Installation Tool, AXIS T90 Illuminators, AXIS T8310 Video Surveillance Control Board, multi-user decoder license pack  |
| <b>Analytics</b>                         | AXIS Video Motion Detection, Autotracking, Active Gatekeeper<br>Audio detection<br>Basic Analytics (not to be compared with third-party analytics): object removed, enter/exit detector, fence detector, object counter<br>Highlight compensation<br>Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://www.axis.com/acap">www.axis.com/acap</a> | <b>Video management software</b>  | AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on <a href="http://www.axis.com/support/downloads">www.axis.com/support/downloads</a>   |
|  |   | <b>Languages</b>                  | English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese  |
|  |   | <b>Warranty</b>                   | Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>   |

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. ([www.openssl.org](http://www.openssl.org)), and cryptographic software written by Eric Young ([ey@cryptsoft.com](mailto:ey@cryptsoft.com)).*

Environmental responsibility:

[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)