

# GRAPHITE Pet

## ADVANCED DIGITAL MOTION DETECTOR

GRAPHITE Pet is a motion detector provided with dual element PIR sensor. Owing to the use of a digital algorithm of motion detection and the temperature compensation function, the device is characterized by reliable operation in a wide range of ambient temperatures as well as high sensitivity and immunity to interference. Interchangeable Fresnel lens and three-step sensitivity control make it possible to adjust the device performance to requirements of the user and the protected premises. An additional feature is the alarm memory: the detector that has detected violation is signaling it by flashing LED, which allows quick identification of the violated partition. GRAPHITE Pet is provided with tamper protection against opening the enclosure. It also has built-in EOL resistors for easy installation and connection to the alarm system.

The main task of the detector is to detect violations in the protected area, but it can also be used to implement the functions of building automation. When the alarm system is not armed, the detector can control turning on the lights, opening or closing the doors, etc.. GRAPHITE Pet can also be successfully used in areas where there are animals weighing up to 15 kg because it is immune to their movements in the supervised partition.

- home pet immunity up to 15 kg
- high quality dual element pyrosensor
- new generation DSP and analysis algorithm
- precise LODIFF Fresnel sealed optics
- digital temperature compensation
- remotely triggered test mode
- alarm latch feature
- build-in EOL resistors



### TECHNICAL DATA

Supply voltage	12 V DC
Detected target velocity	0,3...3 m/s
Operating temperature range	-30...+55 °C
Recommended mounting height	2,4 m
Standby mode current consumption	12 mA
Max. current consumption	14 mA
Weight	76 g
Relay contacts rated load (resistive)	40 mA / 16 V DC
Maximum humidity	93±3%
Dimensions	63 x 96 x 49 mm
Environmental class according to EN50130-5	II
Alarm signaling time	2 s
EOL resistors	2 x 1,1 kΩ
Warm-up period	30 s



The actual appearance of the products may differ from the presented images. Product descriptions are provided in the web service for information purposes only.